

SSV

2120M TRACTOR



VENTRAC

SSV TRACTOR

| | |
|--------------------|---|
| Model | SSV Vanguard Gasoline |
| Stock Codes | 39.61102 |
| Accessory Options: | PTO, Weight Transfer & Rear Work Lights |

Engines

| | |
|---------------------|---------------------------------|
| Engine Manufacturer | Vanguard |
| Engine | 386777 |
| Max Operating Speed | 3600rpm |
| Horsepower | 23 |
| Peak Torque | 32 ft-lbs (43.4 Nm) @ 3,000 RPM |
| Displacement | 627cc |
| Cylinders | 2 |
| Engine Oil | Ventrac Full Synthetic 10W30 |
| Fuel Type | Gasoline |
| Fuel Capacity | 3.3 gal (12.5L) |
| Fuel Economy | 1.0 gal/hr |
| Slope Rating | 10° (18% Grade) |
| Alternator | 20–50 Amps |

Dimensions

| | |
|------------------------------|------------------|
| Weight | 970 lb (440 kg) |
| Weight with accessories kits | 1020 lb (463 kg) |
| Wheelbase | 28 inch (71 cm) |
| Length | 67 inch (171 cm) |
| Width | 34 inch (86 cm) |
| Height | 55 inch (140 cm) |
| Turning Radius | 0 inch (0 cm) |

Electrical

| | |
|--------------------|----------------------|
| Battery | 500 CCA (Group 51R) |
| Voltage | 12 Volts |
| Battery Disconnect | 150A Circuit Breaker |
| Fuses | Mini Fuse |

Hitch and PTO (optional)

| | |
|----------------------------------|----------------------|
| Front Hitch | Ventrac Mount System |
| Electrical PTO clutch with Brake | Warner GT-2000 |

Lighting

| | |
|------------------|----------------------------|
| Head Lights | (2) 1200 Lumens LED Lights |
| Rear Work Lights | (2) 1200 Lumens LED Lights |

Drivetrain

| | |
|------------------------------------|--|
| Type | Hydrostatic |
| Pump | Hydro-Gear tandem, variable displacement piston type |
| Wheel Motors | Parker TJ Geroller |
| Hydraulic Oil Filter (Suction) | 25 Micron, replaceable |
| Hydraulic Oil Filter (Pressurized) | 10 Micron, replaceable |

Instrumentation

| | |
|------------------|--|
| Gauges | Hour Meter, Fuel Level |
| Indicator Lights | PTO, Parking Brake, Low Voltage, Low Oil Pressure |

Controls

| | |
|----------------------|-------------------------|
| Forward/Reverse | Hydraulic Lever Control |
| Attachment Lift | Joystick |
| Auxiliary Hydraulics | Joystick |
| Throttle | Dash Mounted |
| Front Hitch Lock | Hitch Mounted |
| PTO Belt Tensioner | Machine Spring |
| Weight Transfer | 3 Position |
| Steering | Hydraulic Lever Steer |

Tires

| | |
|------------------------|-------------------------------|
| Standard (All Terrain) | 18x8.5-10 (46 x 22 x 25.4 cm) |
|------------------------|-------------------------------|

Travel Speed (F/R)

| | |
|------------|---|
| High Range | 8 mph (12.8 kph) forward 5 mph (8 kph) reverse |
|------------|---|

All specifications subject to change without notice or obligation





The Ventrac SSV makes it easy and efficient to manage snow and ice on sidewalks. The SSV is a dedicated Sidewalk Snow Vehicle with an industry-first 36" working width in order to allow access to the tightest areas of any property. The SSV allows for more reduction of hand labor and walk-behind equipment than ever before. It's also designed with a full arsenal of commercial quality snow removal attachments and de-icing options that are engineered to provide a system that can handle any winter storm. The wait for a proper sidewalk snow machine is finally over.

Standard Features:

- Heated Grips
- Adjustable Operator Pad
- Sealed Electrical System
- Easy Engine Access
- Commercial Grade Engine
- Battery Disconnect Switch
- Tight Turning Radius
- Front Hydraulic Couplers - Drip free
- Heavy Duty Welded Steel Frame
- Full Front & Rear Skid Plates

Optional Accessories Include:

- Adjustable Weight Transfer System
- Power Take Off
- Rear Lighting

Visit www.ventrac.com/accessories for full list.





VENTRAC